



MULTIPURPOSE DRY CHEMICAL FIRE EXTINGUISHERS (STORED PRESSURE TYPE)

The broadened selection job powerful types available so that there is unit for every equipment, from room to a large building. factory, and explosive and combustibles.

SPECIFICATION

MODEL		FP-5D	FP-10D	FP-15D	FP-20D	FP-50D
Weight of Container	Kg.	1.7	2.6	3.4	4.4	20.0
Weight of Agent	Kg.	2.3	4.5	6.8-7.0	9.0-9.5	23.0
Gross Weight	Kg.	4.0	7.1	10.2-10.4	13.4-13.9	43.0
Propellant Gas		N2	N2	N2	N2	N2
Working Pressure	PSI.	195	195	195	195	195
Discharging Time	sec.	10	15	20	25	35
Over all Weight	mm.	380	500	560	590	985
Shell Diameter	mm.	115	138	152	176	230

CLEAN FIRE EXTINGUISHER

MODEL		FP-2N	FP-5N	FP-10N	FP-15N
Weight of Container	Kg.	1.05 Kg.	2.3 Kg.	4.5 Kg.	6.8 Kg.
		0.81 Kg.	1.7 Kg.	2.6 Kg.	3.4 Kg.
Weight of Agent	Kg.	1.05 Kg.	2.3 Kg.	4.5 Kg.	6.8 Kg.
Gross Weight	Kg.	1.86 Kg.	4.0 Kg.	7.1 Kg.	10.2 Kg.
Over all Weight	mm.	307 mm.	380 mm.	500 mm.	560 mm.
Shell Diameter	mm.	90 mm.	228 mm.	138 mm.	152 mm.
		175 PSI	195 PSI	195 PSI	195 PSI
Working Pressure	PSI	(1.34 Mpa)	(1.34 Mpa)	(1.34 Mpa)	(1.34 Mpa)
Discharging Time	Sec.	Approx.	Approx.	Approx.	Approx.
		10 Sec.	10 Sec.	15 Sec.	20 Sec.
Shooting Range	M.	2 M	4-6 M	6-8 M	6-8 M



CO₂ FIRE EXTINGUISHER

MODEL		B5V	B10V	B15V	B20V
Nominal	(LBS)	5	10	15	20
Capacity	(Kilograms)	2.27	4.54	6.8	9.07
U/L Fire Rating		5B : C	10B : C	10B : C	10B : C
Item Part Number		21111	21106	21103	21096
Shipping	(LBS)	15	30	40	51
Weight	(Kilograms)	6.8	13.6	18.1	23.1
	(Inches)	17	19.3	26	26
Unit Height	(Centimeters)	43.2	49.2	66	66
	(Inches)	8.5	10.87	10.87	12
Unit Width	(Centimeters)	21.6	27.6	27.6	30.5



WATER, FOAM & WET CHEMICAL STAINLESS STEEL

MODEL		240	252	B262
Gross Weight	(Approx)	12.5 Kg.	12.5 Kg.	12.5 Kg.
Capacity		2.5 gals.	2.5 gals.	2.5 gals.
Empty		6.6 Kg.	13.2 Kg.	7 Kg.
Discharging Duration		45 Sec	60-65 Sec	107 Sec.
Shooting Range		30-45 ft.	15-20 ft.	10-12 ft.

